

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Problem Image Mailbox.**




FIG. 1









FIG. 2





F15.4




FIG. 5




FIG. 6a




FIG. 6b

Ratio of halo gain to total gain




FIG. 7




FIG. 8 a Planar silicon




FIG. 8

b Planar silicon with 500 Å Au overcoat




FIG. 8 c Planar silicon with 500 Å Al overcoat




FIG. 8 d Pit with depth to pitch ratio of 1 (6 μ m pitch pit)





FIG. 8 e Pit with depth to pitch ratio of 2 (6 mm pitch pit)



Intensity (Normalized to Al)

3.55E-06+
3.23E-06 to 3.55E-06
2.90E-06 to 3.23E-06
2.58E-06 to 2.90E-06
2.26E-06 to 2.58E-06
1.94E-06 to 2.26E-06
1.61E-06 to 1.94E-06
1.29E-06 to 1.61E-06
9.68E-07 to 1.29E-06
6.45E-07 to 9.68E-07
3.23E-07 to 6.45E-07
0.00E+00 to 3.23E-07

FIG. 8 f Inverted Pyramid (6 micron pitch)




FIG. 9 a Planar silicon




FIG. 9b

Planar silicon with 500 Å Au




FIG. 9c Planar silicon with 500 Å Al




FIG. 9 d Pit with depth to pitch ratio of 1





FIG. 9 e Pit with depth to pitch ratio of 2



Intensity (normalized to Al)

5.78E-06+
5.25E-06 to 5.78E-06
4.73E-06 to 5.25E-06
4.20E-06 to 4.73E-06
3.68E-06 to 4.20E-06
3.15E-06 to 3.68E-06
2.63E-06 to 3.15E-06
2.10E-06 to 2.63E-06
1.58E-06 to 2.10E-06
1.05E-06 to 1.58E-06
5.25E-07 to 1.05E-06
0.00E+00 to 5.25E-07

Fig. 9 f Inverted Pyramids




FIG. 10




FIG. 11

Ratio of halo gain to total gain






FIG. 12



Intensity (Normalized to Al)

3.55E-06+
 3.23E-06 to 3.55E-06
 2.90E-06 to 3.23E-06
 2.58E-06 to 2.90E-06
 2.26E-06 to 2.58E-06
 1.94E-06 to 2.26E-06
 1.61E-06 to 1.94E-06
 1.29E-06 to 1.61E-06
 9.68E-07 to 1.29E-06
 6.45E-07 to 9.68E-07
 3.23E-07 to 6.45E-07
 0.00E+00 to 3.23E-07

Fig. 13a 1 μ m Pitch Pits, depth to pitch ratio of 1



Intensity (Normalized to Al)

3.55E-06+
 3.23E-06 to 3.55E-06
 2.90E-06 to 3.23E-06
 2.58E-06 to 2.90E-06
 2.26E-06 to 2.58E-06
 1.94E-06 to 2.26E-06
 1.61E-06 to 1.94E-06
 1.29E-06 to 1.61E-06
 9.68E-07 to 1.29E-06
 6.45E-07 to 9.68E-07
 3.23E-07 to 6.45E-07
 0.00E+00 to 3.23E-07

Fig. 13 b 1 μm Pitch Pits, depth to pitch ratio of 2